Advanced Curtain wall Technique

Drill rig SBN 502 for natural stone and ceramic

Product description

Stationary drilling machine for to drill undercut holes into Natural Stone panels and Ceramic Tiles for fischer FZP-Anchors. Machine is designed for volume production.

Advantages

- Easy to operate
- Economically production of undercut holes, drilling modules can be operated simultaneous
- Versatile use

Technical details

- Solid frame with collect pan
- Multi-directional table rollers for smooth move of panels
- Drill heads continuously adjustable in the direction of the traverse beam
- Drill heads with drill hole depth stoppers and undercut mechanism
- Water / electricity are automatically switched on / off when the drill head is activated / deactivated
- Diamond drilling technique
- Spray-head for panel and machine cleaning



Technical data

Technical data	
Dimensions	Drill rig: 210 x 155 x 160 cm, (W x D x H)
Weights	approx. 480 kg
Table size / Table height	170 x 130 / 80 cm
Maximum load	each table roller Ø60mm: 200 N
Connections	Electricity: 230 V, 16 A Water: ½ inch cross section, at least 3 bar fresh water
Consumption data	Power consumption: ca. 2 kW Water consumption: ca. 3 I/min (idle running)
Panel sizes which can be drilled	Without help of side tables: 157 x 150 x 6 cm (x / y / z)
Precision of drilling position	approx. 1 mm
Drill bit types	FZP B 9 Item-No. 60 713 for FZP-M6 anchors FZP B 11 Item-No. 60 710 for FZP-M8 anchors
Drilling variation	
Options	 Side table Type BST 502 Dimensions: 100 x 125 x 83 cm (W x D x H)

• Weight: ca. 50 kg

Prices / configuration

ACT Service

- vveight: ca. 50 kg
- for purchase and hire on demand

fischerwerke GmbH & Co. KG Werk Altheim · Hindenburgstr. 81 · D-72160 Horb Phone +49 (0)74 43 12-45 53 · Fax +49 (0)74 43 12-49 07 act@fischer.de · www.fischer.de